

GARRARD COUNTY ROAD DEPARTMENT
SPECIFICATIONS FOR BITUMINOUS CONCRETE BASE AND/OR
SURFACE IN PLACE

Bituminous Concrete Base and /or Surface is to meet Kentucky Department of Transportation specifications.

Certified gradation and extraction test(s) to be provided by a certified technician as approved by the Kentucky Department of Transportation for each days production of Bituminous Concrete Base.

Any gradation or extraction test that falls outside the Kentucky Department of Transportation master specification tolerance range is subject to penalties as outlined in the Kentucky Department of Transportation Specifications.

Tack oil. SS-1H, is to be included in the price per ton and to be based on .07-.15 gallons per square yard.

Roads to be paved will be a minimum of 9 feet wide and 1500 feet long. The laying depth will be 2 inches compacted Bituminous Concrete Base, and 1" to 1 ½" resurface.

All material must be applied with a self-propelled Bituminous paver and rolled while hot with a 10-ton tandem roller. All equipment must meet Kentucky State Highway Department specifications and be in good working condition.

The contractor will be required to provide a certificate of Workmen's Compensation Insurance and Public Liability coverage. A certificate of Public Liability and Property Damage Insurance coverage on all vehicles used in this operation is also required before commencing work on this contract.

***No mileage fee accepted over and above bid price.**